

# Product data sheet


## Ilme connectoren

surface mounting housing, high, size 57.27, T-TYPE C plastic, 2 levers, 1xM25 side, PE-jumper



TAPC 10.25B

<https://www.ac-solutions.be/nl/product/tapc1025b>



## Specificaties

### General characteristics

|                             |                          |
|-----------------------------|--------------------------|
| Enclosure type              | Surface mounting housing |
| Size                        | 57.27                    |
| Enclosure series            | T-TYPE /C                |
| Closing type                | With 2 levers            |
| Locking mechanism           | Double locking levers    |
| Protection degree           | IP66 / IP69              |
| Ambient lower temperature   | -50 °C                   |
| Ambient upper temperature   | 70 °C                    |
| Operation lower temperature | -50 °C                   |
| Operation upper temperature | 70 °C                    |
| Cable entry type            | side cable entry         |
| Cable entry size            | M25                      |
| Position cable feed         | Side entry               |
| Height                      | 80 mm                    |
| Width                       | 45 mm                    |
| Length                      | 82 mm                    |

## Material

# Product data sheet

## Ilme connectoren

surface mounting housing, high, size 57.27, T-TYPE C plastic, 2 levers, 1xM25 side, PE-jumper



|                                                            |               |
|------------------------------------------------------------|---------------|
| Material housing                                           | Thermoplastic |
| Coating housing                                            | Uncoated      |
| Inflammability class of insulation material acc. with UL94 | V0            |