

Product data sheet


Techno connectoren
Mini plug connector Screw



IP66/IP68 xDRY

THB.387.A4A.XD

<https://www.ac-solutions.be/nl/product/thb387a4axd>



Specificaties

General Characteristics

Series	TEEPLUG
Subseries	TH387
Number of contacts	4
Gender	Male
Contact terminals	Screw
Cable section	0,5 - 1,5 mm ²
Min-max cable diameter	7,0 - 12,0 mm
Protection degree	IP66/IP68
Protection degree details	IP68 (30m/3h)
Lower temperature	-40 °C
Upper temperature	+125 °C
Pollution degree	2
Standards	EN61984:2009
Tracking index	PTI 175

Product data sheet

Techno connectoren Mini plug connector Screw



Remark*

Xdry connectors protected from water and dust (IP68) with anti-condensation barrier. The xDry system prevents the damp inside the cable from entering the connection and proceeding towards the device installed.

Electrical parameters

Rated current	17.5 A
Rated voltage	500 V
Impulse withstand voltage	4 kV

Material

Impulse withstand category	II
Connector housing	PA66 GF UL94 V0
Cable glands	PA66 UL94 V2
Grommets	TPE
Co-moulded seals	TPE
Contact screw terminals	Brass
Standard/Piercing screws	Steel