

# Product data sheet

## Techno connectoren

### Current distributor Plug & Socket screw



## IP66/IP68

THH.625.A2B

<https://www.ac-solutions.be/nl/product/thh625a2b>



## Specificaties

### General Characteristics

|                     |                                                                       |
|---------------------|-----------------------------------------------------------------------|
| Series              | TEEBOX CURRENT DISTRIBUTORS                                           |
| Subseries           | TH625                                                                 |
| Number of contacts  | 2                                                                     |
| Contact terminals   | Screw                                                                 |
| Cable entries/exits | 4 ways                                                                |
| Protection degree   | IP66/IP68                                                             |
| Lower temperature   | -40 °C                                                                |
| Upper temperature   | +100 °C                                                               |
| Pollution degree    | 2                                                                     |
| Note                | Plug and socket connectors are not included, To be ordered separately |
| Standards           | EN61984:2009                                                          |
| Tracking index      | PTI 175                                                               |

### Electrical parameters

|               |      |
|---------------|------|
| Rated current | 10 A |
|---------------|------|

# Product data sheet

## Techno connectoren

### Current distributor Plug & Socket screw



|                           |        |
|---------------------------|--------|
| Rated voltage             | 500 V  |
| Impulse withstand voltage | 2.5 kV |

## Material

|                                   |                 |
|-----------------------------------|-----------------|
| Impulse withstand category        | II              |
| Distributor and connector housing | PA66 GF UL94 V0 |
| Seals                             | TPE             |
| Contact screw terminals           | Silver plated   |