

Product data sheet

Yamaïchi connectoren


Standard wall mounted socket - front mounting




YCP-BWA12ACX-06FSEEX-000X

YCP-BWA12ACX-06FSEEX-000X

<https://www.ac-solutions.be/nl/product/ycpbwa12acx06fseex000x>



Dimensions [mm]			
D1= 14.0	L1= 20.1	W1= 10.5	
	L2= 17.9	W2= 14.0	
	L3= 11.1		
	L4= 1.6		
		M1= M12x1.0	
	L7= 2.5		



Specificaties

General Characteristics

Pin count	6 Pins
Size	Size 12
Housing variant	Standard
Insulator Variant	Standard
IP Grade (to contact)	IP50
IP Grade (to housing)	IP50
Mating cycles	5000 Times
Min. operating temperature	-40 °C
Max. operating temperature	+120 °C
Short Term Max. Temp	+260 °C
Vibration [Hz]	20 [10 Hz - 2000 Hz]
Shock resistance	50 [6 ms]
Salt Spray Corrosion	>144 Hours
Shielding (10 MHz)	>75 Db
Shielding (1 GHz)	>55 Db
Contact Diameter	0.7 mm

Product data sheet

Yamaïchi connectoren

Standard wall mounted socket - front mounting



Terminal cross section	Max AWG 22 / 0,34 mm ²
Contact Type	Female: Solder Contacts
RoHS	2011/65/EU (2015/863/EU)

Electrical Parameters

Current rating per contact	7 A
Test Voltage Contact-Contact RMS	0.8 kV
Test Voltage Contact-Shell RMS	0.8 kV
Contact Resistance	6,5 ?

Material

Connector type digit	WA
Housing Material	Brass
Housing surface	Chrome
Contact Material and Surface	CuZn38Pb2 / min 0.75µm Au
Insulator Material	PEEK (UL)