# Product data sheet

## Higo connectoren - Z1115A

### Female cable connector

Z1115AM P 00 DU 1000
https://www.ac-solutions.be/nl/product/z1115amp00du1000




## Specificaties

### General Characteristics

| | |
|---|---|
| **Number of contacts** | 11 (3+8) |
| **Connector shape** | Plug |
| **Gender** | Female |
| **Color** | Black |
| **Upper temperature** | 80 °C |
| **Lower temperature** | -25 °C |
| **Protection degree** | IP67 |
| **Mating cycles (times)** | 200 Times |
| **Connector diameter** | 15 mm |
| **Fitting length** | 70 mm |
| **Cable Length** | 1000 mm |
| **Cable diameter** | 7.5 mm |
| **Wire section** | 3 x 2,5 + 8 x 0,14 |
| **Remark** | Other cable length/type on request |

# Product data sheet

## Higo connectoren - Z1115A

### Female cable connector

## Electrical Parameters

| | |
|---|---|
| **Rated current** | 25 / 2 A |
| **Rated voltage** | 48 V AC / 60 V DC |
| **Max. insulation resistance (M?)** | ?20 M? |
| **Max. contact resistance (M?)** | ?10 m? |

## Material

| | |
|---|---|
| **Material jacket** | PVC |
| **Insulation wire** | PTFE |
| **Material of contact** | Copper Alloy |
| **Contact plating** | Gold over Nickel |