#### **Product sheet**

## Automation technology - Speciality connectors



Product

Contacts: 4, Female angled connector, plastic lock, screw terminal connection, with UL approval

Article number


Area


M12-B Series 715 99 0430 05 04

Pole

4







You can find the item description and assembly instruction on the next page.

### **Technical** data

#### **Common values**

Connector Design Connector locking system Termination Wire gauge (mm) Wire gauge (AWG) Cable outlet Upper temperature Lower temperature Female angled connector screw

Screwing 0.75 mm<sup>2</sup> 18 4 - 6 mm 85 °C -40 °C

Cable data

material housing Insulation single lead Single lead structure Conductor resistance Bending radius cable fixed Bending radius cable movable -

#### **Electrical values**

250 V Rated voltage 2500 V Rated impulse voltage Pollution degree 3 Overvoltage category Ш Material group П Rated current (40°C) 4 A Volume resistivity  $\leq 8 \, \text{m}\Omega$ not shielded EMV compliance Degree of protection IP67 Mechanical operation > 50 mating cycles

#### **Material**

Material of contact Contact plating Material of contact body Material of housing CuZn (Brass) CuSnZn (Optaloy)

PA PΔ r

PA, nickel-plated zinc die casting/ PA

cable outlet: 4 - 6 mm, Contacts: 4, Female angled connector, plastic lock, screw terminal connection, with UL approval



#### **Product sheet**

# Automation technology - Speciality connectors



Product

Contacts: 4, Female angled connector, plastic lock, screw terminal connection, with UL approval

Area Article number M12-B Series 715 99 0430 05 04

Pole

4

