

Product	Contacts 4, female panel mount connector IP 67, shielded	Area	Push-Pull IP67 Series 430
Pole	4	Article number	09 4912 00 04

Illustration	Scale drawing	Contact Arrangement															
		<table border="1" style="margin-left: 20px;"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>-1,11</td> <td>-1,11</td> </tr> <tr> <td>2</td> <td>-1,11</td> <td>1,11</td> </tr> <tr> <td>3</td> <td>1,11</td> <td>1,11</td> </tr> <tr> <td>4</td> <td>1,11</td> <td>-1,11</td> </tr> </tbody> </table>		X	Y	1	-1,11	-1,11	2	-1,11	1,11	3	1,11	1,11	4	1,11	-1,11
	X	Y															
1	-1,11	-1,11															
2	-1,11	1,11															
3	1,11	1,11															
4	1,11	-1,11															

You can find the item description and assembly instruction on the next page.

Technical data

Common values

Connector Design	Female panel mount connector
Connector locking system	Push-Pull
Termination	Solder
Wire gauge (mm)	0.25 mm ²
Wire gauge (AWG)	24
Upper temperature	85 °C
Lower temperature	-40 °C

Cable data

material housing	-
Insulation single lead	-
Single lead structure	-
Conductor resistance	-

Electrical values

Rated voltage	125 V
Rated impulse voltage	1500 V
Pollution degree	2
Overvoltage category	I
Material group	II
Rated current (40°C)	3 A
Volume resistivity	≤ 5 mΩ
EMV compliance	shieldable
Degree of protection	IP67
Mechanical operation	> 500 mating cycles

Material

Material of contact	CuSn (Bronze)
Contact plating	Au (Gold)
Material of contact body	PBT, PA
Material of housing	CuZn (Brass nickel-plated)

Contacts: 4, Female panel mount connector IP 67, shielded

Product

Contacts 4, female panel mount connector

Area

Push-Pull IP67 Series 430


Pole

IP 67, shielded
4

Article number

09 4912 00 04

Item description



Installation instructions / Mounting cutout

